"© 2023 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works."

3 4

5 6 7

8

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS FOR VIDEO TECHNOLOGY, VOL. XX, 2023

# Egocentric Early Action Prediction via Transformer-based Dual Action Prediction

Weili Guan, Member, IEEE, Xuemeng Song, Senior Member, IEEE, Kejie Wang, Haokun Wen, Hongda Ni, Yaowei Wang, Member, IEEE, Xiaojun Chang, Senior Member, IEEE

Abstract-Egocentric early action prediction, which aims to recognize the on-going action in the video captured in the first-person view as early as possible before the action is fully executed, is a new yet challenging task due to the limited partial video input. Pioneer studies focused on solving this task with LSTMs as the backbone and simply compiling the observed video segment and unobserved video segment into a single vector, which hence suffer from two key limitations: lack the non-sequential relation modeling with the video snippet sequence and the correlation modeling between the observed and unobserved video segment. To address these two limitations, in this paper, we propose a novel TransfoRmer-based duAl aCtion prEdiction (TRACE) model for the task of egocentric early action prediction, which consists of two key modules: the early (observed) segment action prediction module and the future (unobserved) segment action prediction module. Both modules take Transformer encoders as the backbone for encoding all the potential relations among the input video snippets, and involve several single-modal and multi-modal classifiers for comprehensive supervision. Different from previous work, each of the two modules outputs two multi-modal feature vectors: one for encoding the current input video segment, and the other one for predicting the missing video segment. For optimization, we design a two-stage training scheme, including the mutual enhancement stage and end-to-end aggregation stage. The former stage alternatively optimizes the two action prediction modules, where the correlation between the observed and unobserved video segment is modeled with a consistency regularizer, while the latter seamlessly aggregates the two modules to fully utilize the capacity of the two modules. Extensive experiments have demonstrated the superiority of our proposed model. We have released the codes and the corresponding parameters to benefit other researchers<sup>1</sup>.

## Index Terms—Egocentric Early Action Prediction; Transformer; Mutual Enhancement

This work was supported in part by the Shandong Provincial Natural Science Foundation (No.:ZR2022YQ59); in part by Australian Research Council (ARC) Discovery Early Career Researcher Award (DECRA) under DE190100626. (Corresponding author: Xuemeng Song.)

W. Guan is with the Department of Data Science and Artificial Intelligence, Monash University, Clayton, 3800, Australia, and also with the AI Research Center, Pengcheng Laboratory, Shenzhen, 518055, China (e-mail: honeyguan@gmail.com).

X. Song is with the School of Computer Science and Technology, Shandong University, Tsingtao, 266000, China (e-mail: sxmustc@gmail.com).

K. Wang, H. Wen, and H. Ni are with the School of Computer Science and Technology, Harbin Institute of Technology (Shenzhen), 518055, China (e-mail: kjwang.henry@gmail.com, whenhaokun@gmail.com, nihongda.hit@gmail.com).

Y. Wang is with the AI Research Center, Pengcheng Laboratory, Shenzhen, 518055, China (e-mail: wangyw@pcl.ac.cn).

X. Chang is with the Faculty of Engineering and Information Technology, University of Technology Sydney, Sydney, 2007, Australia (e-mail: cxj273@gmail.com).

<sup>1</sup>https://trace729.wixsite.com/trace.



Fig. 1. Comparison between the tasks of egocentric action recognition and egocentric early action prediction.

# I. INTRODUCTION

**7** IDEO action recognition is an essential research problem in computer vision domain, which aims to classify the action of the person in the video segment. Early studies [1]-[3] focus on the action recognition for videos recorded in the third-person view. Later, with the rapid development of wearable devices, increasing research efforts have been dedicated to the action recognition [4]-[7] for videos recorded in the first-person view, *i.e.*, egocentric action recognition. Moreover, in many real-world scenarios, like autonomous driving [8], [9], we may expect to recognize the action as early as possible. Accordingly, several pioneer studies have paid attention to the new task of egocentric early action prediction [10]-[12]. As shown in Figure 1, different from the egocentric action recognition whose input is the fully observed video segment, egocentric early action prediction aims to recognize the on-going action in the video captured in the first-person view as early as possible. In other words, the input for egocentric early action prediction is the partial video segment with incomplete action execution.

Although the pioneer research studies [13]–[16] on egocentric early action prediction have achieved promising progress, they suffer from two key limitations.

• L1: Lack the non-sequential relation modeling among video snippets. Existing studies mainly utilize LSTMs to encode the video segment, which can capture the temporal sequential relation modeling among video snippets. Nevertheless, LSTMs cannot model the non-sequential relations among video snippets well. For example, there may be some correlations among discrete video snippets at different time steps. Such correlations could be hard to be captured by LSTMs.

# • L2: Lack the correlation modeling between the observed and unobserved video segment. Although existing studies have incorporated the future (unobserved) video segment to enhance the representation learning of early (observed) video segment in the training phrase, they entangled the clues in both observed and unobserved segments into a single vector, and overlook the correlation modeling between the two video segments. Intuitively, we can predict the person's following behavior in the unobserved video segment based on the observed video segment, and vice versa.

To address these limitations, we propose a novel TransfoRmer-based duAl aCtion prEdiction (TRACE) model for the task of egocentric early action prediction, which consists of two key modules: the early segment action prediction module and the future segment action prediction module. The former aims to predict the person's action based on the early observed video segment, while the latter targets predicting that based on the future unobserved video segment. Both modules share the same architecture. Specially, each module is composed by a Transformer-based video encoder and several single-modal and multi-modal action classifiers. Moreover, the video encoder in each module consists of M Transformer subencoders corresponding to the single-modal feature encoding, as well as two fully connected layers for deriving two multi-modal features for encoding the current input video segment and the missing video segment, respectively. The motivation for using Transformer lies in its powerful capability in the non-sequential relation modeling in many computer vision tasks [17], [18]. For optimization, we design a two-stage training paradigm that optimizes the model through two stages: mutual enhancement stage and end-to-end aggregation stage. The goal of the former stage is to alternatively train the early and future segment action prediction modules by allowing the knowledge transfer between the two modules, while that of the latter stage is to seamlessly aggregate the two modules to promote the final model performance.

Our main contributions can be summarized threefold:

- We present a novel Transformer-based dual action prediction model for the task of egocentric early action prediction. To the best of our knowledge, we are the first to incorporate Transformer architecture to enhance the performance of egocentric early action prediction.
- We devise a dual action prediction model, where we take into account the coherence of the full video segment and assume that the feature of the future video segment can be inferred based on the early video segment, while that of the early video segment can be also inferred by mining the future video segment.
- We design a two-stage optimization scheme, including the mutual enhancement stage and end-to-end aggregation stage. The former stage allows the knowledge transferring between the two action prediction modules, while the latter one fully utilizes the capacity of the two modules. Extensive experiments have demonstrated the superiority of our proposed model.

# II. RELATED WORKS

Our work is related to early action prediction and Transformer in vision.

# A. Early Action Prediction

According to the manner of the video being recorded, existing early action prediction studies can be generally classified into two groups: early action prediction in the third-person vision [3], [11], [12], [19], [20], and that in the first-person vision. Previous studies mainly focus on the former group. For example, Kong et al. [12], [20] exploited the abundant sequential context information to enrich the feature representations of the given partial videos in the context of early action prediction. In addition, Wang et al. [10] presented a teacher-student learning framework that distills progressive knowledge from an action recognition network for an early action prediction network. Moreover, Cai et al. [11] resorted to transferring knowledge from full videos to partial videos by a two-stage learning framework, which learns the feature embeddings and action classifier based on the full videos in the first stage and then transfers the knowledge obtained by the first stage to the counterpart (i.e., the feature embedding and action classifier learning based on the partial videos) in the second stage. Later, owing to the rapid development of multi-sensor wearable computing platforms, several research efforts have been dedicated to the egocentric early action prediction, where the input video is recorded in the first-person view. Initially, the egocentric early action prediction task was introduced by Furnari et al. [13], and the authors proposed a Rolling-Unrolling LSTM architecture [14], which can predict egocentric actions at multiple temporal scales, to solve this task. Recently, Zheng et al. [15] presented an adversarial knowledge distillation scheme for the task of egocentric early action prediction, which also adopts a teacher network for learning the comprehensive video representation based on the full video segment, and a student network for predicting the action only based on the partial video segment.

Although great success has been achieved by these studies, existing methods have two key limitations: lack the non-sequential relation modeling among video snippets, and lack the correlation modeling between the observed and unobserved video segments. To address them, we propose the TRACE model, which incorporates the Transformer architecture to enhance the correlation modeling among video snippets, and adopt dual action prediction models to promote the correlation modeling between the observed and unobserved video segments for boosting the egocentric early action prediction performance.

# B. Transformer in Vision

The Transformer is a deep learning model that adopts the self-attention mechanism, adaptively weighting the significance of each part of the input data. It was first proposed in the field of natural language processing (NLP) [21]. Inspired by its exemplary performance on representation learning, it has also been widely used in various computer vision tasks, such as image recognition [22], [23], image captioning [24], [25], object

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59 60 IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS FOR VIDEO TECHNOLOGY, VOL. XX, 2023

detection [26], [27], and video understanding [17], [18], [28]. For instance, Zhao *et al.* [27] proposed a Transformer-based vote refinement model to cultivate the voting results and improve the performance of 3D object detection. In addition, Yu *et al.* [24] introduced the multi-modal Transformer model to deal with the multi-view visual representations, which highly improves the image captioning performance. Besides, Girdhar *et al.* [18] presented an end-to-end attention-based video Transformer for predicting the future actions given previously observed video. Although the Transformer has made outstanding achievements in these tasks, it has never been explored in the task of egocentric early action prediction. Therefore, in this work, we incorporate the Transformer to enhance the performance of egocentric early action prediction.

# III. METHODOLOGY

In this section, we first formulate the research problem, and then detail the components of our proposed transformer-based dual action prediction scheme.

## A. Problem Formulation

In this work, we focus on tackling the problem of egocentric early action prediction. It aims to predict the person's action by observing only a few early video frames from the first-person view. Formally, suppose  $\mathcal{V} = \{V_1, V_2, ..., V_K\}$  is an egocentric video segment consisting of K snippets, and  $\mathbf{y} \in \mathbb{R}^N$  denotes the one-hot action label vector of the video segment, where N is the number of total action label classes. In particular, we employ the first k snippets  $\mathcal{V}_k = \{V_1, V_2, ..., V_k\}$  as the given partial video segment, where  $k \in [1, K]$  denotes the progress level of  $\mathcal{V}_k$ . We use k/K to denote the observation ratio. Each snippet  $V_k$  involves M modalities, such as audio signals, visual content, flow content and the object labels. Let  $\mathbf{x}_m^j \in \mathbb{R}^{d_0^m}$ denote the feature vector of the *j*-th snippet regarding the *m*-th modality, where  $j = 1, \dots, K$ . In this work, we aim to learn a model  $\mathcal{G}(\cdot)$  to predict the action class for a given partial video segment. Mathematically, this task can be formulated as follows.

$$\hat{\mathbf{y}} = \mathcal{G}(\mathcal{X}_1^k, \mathcal{X}_2^k, \cdots, \mathcal{X}_M^k | \Theta), \tag{1}$$

where  $\mathcal{X}_m^k = {\mathbf{x}_m^1, \mathbf{x}_m^2, \cdots, \mathbf{x}_m^k}$  denotes the feature sequence of the partial video segment  $\mathcal{V}_k$  regarding the *m*-th modality.  $\Theta$ is the to-be-learned parameters of the model  $\mathcal{G}(\cdot)$  and  $\hat{\mathbf{y}} \in \mathbb{R}^N$ is predicted action label vector by the model  $\mathcal{G}(\cdot)$ .

## B. Summary

In this work, we aim to timely predict the action of the person in the egocentric video only based on its early video snippets. In particular, we propose a Transformer-based dual action prediction model, which consists of two key modules: the early segment action prediction module  $\mathcal{P}^o$  and future segment action prediction module  $\mathcal{P}^u$ . The former takes the given partial video segment as the input, while the latter takes the future video segment as the input. These two modules share the same network architecture. One major novelty of our model is that we take into account the coherence of full video segment, and assume that the feature of the future

video segment can be inferred based on the early video segment, while that of early video segment can be also inferred by mining the future video segment. Accordingly, each module outputs two multi-modal features: one used for encoding the current input video segment, and the other one used for predicting the missing video segment. Notably, to adapt the Transformer encoder to our context, we adopt the autoregressive pre-training for each Transformer encoder.

For the model optimization, we propose the two-stage training paradigm, which optimizes the model through two stages: mutual enhancement stage and end-to-end aggregation stage. In the former stage, the early and future segment action prediction modules learn from each other, so that both of them can infer the missing part of video and hence gain a comprehensive understanding of the video. In the latter stage, these two modules are seamlessly aggregated to deal with the task of egocentric early action prediction.

# C. Network Structure

Next, we describe the two key components of each module: Transformer-based video encoder and action classifiers.

1) Transformer-based Video Encoder: Since the underlying philosophy for the design of the two modules is similar, we here take the video encoder of the early segment action prediction module  $\mathcal{P}^o$  as an example.

Existing methods on egocentric early action prediction mainly adopted LSTMs to encode the sequence of the video snippets. Nevertheless, it is known that LSTMs cannot capture the long-term temporal dependencies well and can only model the sequential relations among video snippets. Beyond that, we resort to Transformer, which has shown great success in many computer vision tasks [22], [26], [29], [30]. Different from LSTMs, Transformer can flexibly model the relationship among different video snippets with the multi-head self-attention mechanism. In particular, we introduce a specific Transformer to encode each modality of the video snippets. Formally, let  $\mathcal{T}_m^o$  denote the Transformer encoder of the *m*-th modality which consists of several identical layers. Each layer has two sub-layers: one corresponds to a multi-head self-attention mechanism and the other one refers to a feed-forward network. Then we feed the feature sequence of the k snippets in the observed video segment regarding the *m*-th modality  $\{\mathbf{x}_m^1, \mathbf{x}_m^2, ..., \mathbf{x}_m^k\}$  into it. For each modality, we also introduce a to-be-learned [CLS] token  $\mathbf{x}_m^{[\text{CLS}],o}$  to aggregate the global feature of the m-th modality. According to Transformer, we add the to-be-learned positional embedding  $\mathbf{p}_m^j \in \mathbb{R}^{d_0^m}$ , where  $j = 0, \cdots, k$ , to the [CLS] token along with each feature vector. Mathematically, we have,

$$\mathbf{z}_{m,k}^{o} = \mathcal{T}_{m}^{o}([\mathbf{x}_{m}^{[\text{CLS}],o} + \mathbf{p}_{m}^{0}; \mathbf{x}_{m}^{1} + \mathbf{p}_{m}^{1}; ...; \mathbf{x}_{m}^{k} + \mathbf{p}_{m}^{k}]), \quad (2)$$

where  $\mathbf{x}_m^{[\text{CLS}],o} \in \mathbb{R}^{d_0^m}$  denotes the [CLS] token of the *m*-th modality.  $\mathbf{z}_{m,k}^o \in \mathbb{R}^{d_1}$  is the encoded feature of the given early video segment  $\mathcal{V}_k$  regarding the *m*-th modality, and  $d_1$  is the dimension of the hidden layer.

# IEEE Transactions on Circuits and Systems for Video Technology



Fig. 2. Illustration of the proposed TRACE model, which consists of two key modules: the early segment action prediction module and future segment action prediction module. The proposed model is optimized through two stages: mutual enhancement stage and end-to-end aggregation stage.

We then concatenate all the encoded features of the M modalities and use a fully-connected layer to derive the final encoded feature of the given early video segment as follows,

$$\mathbf{h}_{k}^{o} = \mathbf{W}^{o} \mathbf{z}_{k}^{o} + \mathbf{b}^{o}, \tag{3}$$

where  $\mathbf{z}_k^o = [\mathbf{z}_{1,k}^o; \cdots; \mathbf{z}_{M,k}^o] \in \mathbb{R}^{M*d_1}$  is the concatenation of all the encoded features.  $\mathbf{h}_k^o \in \mathbb{R}^{d_2}$  is the final encoded feature of the early video segment, where  $d_2$  is the final encoded feature dimension.

Previous work on egocentric early action prediction focuses on encoding the given partial video segment into a single vector. Most of them rely on the single vector to capture the information of the observed video segment. Obviously, this manner would miss the information of the future video segment, which undoubtedly benefits the action prediction of the video. Notably, although the future video segment is unavailable in testing, it can be still used in the training phrase. It is worth mentioning some efforts [15] have been dedicated to utilize the future video segment in the training phrase with the knowledge distillation technique. However, they also use a single vector to compile both the observed and unobserved video segments. Different from previous studies, we propose to encode the partial video with two separate features: one used for delivering the content of the observed partial video segment, and the other one used for indicating the content of the unobserved future video segment. In this manner, the features for the two video segments can be disentangled, which could benefit the feature encoding. Therefore, we introduce another fully connected layer to predict the feature of the

future video segment based on the observed early video segment as follows,

$$\tilde{\mathbf{h}}_{k}^{u} = \tilde{\mathbf{W}}^{o} \mathbf{z}_{k}^{o} + \tilde{\mathbf{b}}^{o}, \tag{4}$$

where  $\tilde{\mathbf{h}}_k^u \in \mathbb{R}^{d_2}$  is the predicted future feature for the given partial video segment.

Similar to the structure of  $\mathcal{P}^o$ , the video encoder of the future video processing module  $\mathcal{P}^u$  is composed of MTransformers to encode the M different modalities, and two fully-connected layers for learning the features of the previous video segment and the unobserved future video segment, respectively. Specifically, we feed the future video segment into  $\mathcal{P}^u$  and have:

$$\begin{cases} \mathbf{z}_{m,k}^{u} = \mathcal{T}_{m}^{u}([\mathbf{x}_{m}^{[\text{CLS}],u} + \mathbf{p}_{m}^{0}; \mathbf{x}_{m}^{k+1} + \mathbf{p}_{m}^{1}; ...; \mathbf{x}_{m}^{K} + \mathbf{p}_{m}^{K-k}]), \\ \mathbf{z}_{k}^{u} = [\mathbf{z}_{1,k}^{u}; ...; \mathbf{z}_{M,k}^{u}], \\ \mathbf{h}_{k}^{u} = \mathbf{W}^{u} \mathbf{z}_{k}^{u} + \mathbf{b}^{u}, \\ \tilde{\mathbf{h}}_{k}^{o} = \tilde{\mathbf{W}}^{u} \mathbf{z}_{k}^{u} + \tilde{\mathbf{b}}^{u}, \end{cases}$$
(5)

where  $\mathcal{T}_m^u$  is the Transformer for encoding the *m*-th modality of the unobserved video segment,  $\mathbf{x}_m^{[\text{CLS}],u} \in \mathbb{R}^{d_0^m}$  denotes the [CLS] token of the *m*-th modality, used for aggregating the global feature of this modality,  $\mathbf{z}_{m,k}^u \in \mathbb{R}^{d_1}$  is the encoded feature of the modality *m* for the unobserved segments,  $\mathbf{h}_k^u \in \mathbb{R}^{d_2}$  and  $\tilde{\mathbf{h}}_k^o \in \mathbb{R}^{d_2}$  are the encoded feature of the future unobserved video segment and predicted feature of the previous observed video segment, respectively.

**Pre-training.** To adapt the Transformer encoder to our egocentric early action prediction task and further improve

4

60

2

3

4

5

6 7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26 27 28

29

30

31

32

33

34 35

36

37

38

39

40

41

42

43 44

45 46

47

48

49

50

51

52

53

54

55

56

57

58

59 60



Fig. 3. Pre-traing for the Transformer encoder regarding the *m*-th modality.

the model performance, we introduce the autoregressive pre-training [31], [32] to particularly improve the feature encoding capability of the Transformer encoders in our two modules. Figure 3 illustrates the pre-training paradigm for the Transformer encoder regarding the *m*-th modality. Specifically, for each Transformer encoder  $\mathcal{T}_m, m = 1, \dots, M$ , we expect it can predict the feature of *m*-th modality for the next snippet based on the previous *k* snippets of the video sequence. Hence the Transformer encoder can fully understand the context of the video snippet sequence.

Mathematically, the pre-training process can be formulated as follows,

$$\mathbf{z}_{m,k} = \mathcal{T}_m([\mathbf{x}_m^{[\text{CLS}]} + \mathbf{p}_m^0; \mathbf{x}_m^1 + \mathbf{p}_m^1; ...; \mathbf{x}_m^k + \mathbf{p}_m^k]), \quad (6)$$

where  $\mathbf{x}_m^{[\text{CLS}]} \in \mathbb{R}^{d_0^m}$  is the [CLS] token feature of the modality m, used to aggregate the information of the entire video sequence.  $\mathbf{x}_m^i \in \mathbb{R}^{d_0^m}$ ,  $i \in [1, k]$  is the feature of the *i*-th video snippet with respect to the *m*-th modality.  $\mathbf{p}_m^i \in \mathbb{R}^{d_0^m}$ ,  $i \in [0, k]$  is the positional embedding.  $\mathbf{z}_{m,k} \in \mathbb{R}^{d_1}$  is the encoded feature for the input partial video segment (*i.e.*, the first k snippets).

We then use a fully-connected layer  $\mathcal{F}_m : \mathbb{R}^{d_1} \mapsto \mathbb{R}^{d_0^m}$  to predict the feature of the next snippet (*i.e.*,  $\mathbf{x}_m^{k+1}$ ) based on the encoded feature  $\mathbf{z}_{m,k}$  of the previous k snippets. Finally, we adopt the L2 norm loss function for optimization as follows,

$$\begin{cases} \hat{\mathbf{x}}_{m}^{k+1} = \mathbf{W}_{m}^{pre} \mathbf{z}_{m,k} + \mathbf{b}_{m}^{pre}, m = 1, \cdots, M \\ \mathcal{L}_{m}^{pre} = \sum_{k=1}^{K-1} \|\hat{\mathbf{x}}_{m}^{k+1} - \mathbf{x}_{m}^{k+1}\|^{2}, \end{cases}$$
(7)

where  $\mathbf{W}_{m}^{pre}$  and  $\mathbf{b}_{m}^{pre}$  are parameters of the fully-connected layer.  $\hat{x}_{m}^{k+1}$  is the predicted feature of the next snippet.

The learned parameters of these M Transformer encoders will be used for the parameter initialization. Specifically, for each modality m, the Transformer encoder  $\mathcal{T}_m^o$  in the early segment action prediction module and  $\mathcal{T}_m^u$  in the future segment action prediction module are both initialized with parameters of  $\mathcal{T}_m$  to enhance their encoding capabilities.

2) Action Classifier: In order to ensure the features extracted by  $\mathcal{P}^o$  can contain discriminant information for action classification, we introduce a classifier  $\mathcal{C}^o$  with the cross-entropy loss function as follows,

$$\begin{cases} \mathbf{a}_{k}^{o} = \mathbf{W}^{o} \mathbf{h}_{k}^{o} + \mathbf{b}^{o}, \\ \mathcal{L}_{k}^{o} = \mathrm{CE}(\mathbf{a}_{k}^{o}, \mathbf{y}), \end{cases}$$
(8)

where  $\mathbf{W}^o$  and  $\mathbf{b}^o$  are the to-be-learned parameters of the classifier.  $\mathbf{a}_k^o \in \mathbb{R}^N$  is the predicted action label vector based on the learned final feature of the observed video segment.

Similarly, for the future segment action prediction module  $\mathcal{P}^u$ , we also introduce a classifier  $\mathcal{C}^u$  as follows,

$$\begin{cases} \mathbf{a}_{k}^{u} = \mathbf{W}^{u} \mathbf{h}_{k}^{u} + \mathbf{b}^{u}, \\ \mathcal{L}_{k}^{u} = \mathrm{CE}(\mathbf{a}_{k}^{u}, \mathbf{y}), \end{cases}$$
(9)

where  $\mathbf{W}^u$  and  $\mathbf{b}^u$  are the to-be-learned parameters of the classifier.  $\mathbf{a}_k^u \in \mathbb{R}^N$  is the predicted action label vector based on the learned final feature of the future video segment.

As to supervise the feature prediction of the future video segment by  $\mathcal{P}^o$ , we feed the predicted feature of the future video segment into the action classifier of  $\mathcal{P}^u$ , and use crossentropy loss for optimization. Conversely, we also feed the predicted feature of the previous video segment by the future segment action prediction module into the action classifier of early segment action prediction module for optimization. Formally, we have,

$$\begin{cases} \tilde{\mathbf{a}}_{k}^{u} = \mathbf{W}^{u} \tilde{\mathbf{h}}_{k}^{u} + \mathbf{b}^{u}, \\ \tilde{\mathbf{a}}_{k}^{o} = \mathbf{W}^{o} \tilde{\mathbf{h}}_{k}^{o} + \mathbf{b}^{o}, \\ \tilde{\mathcal{L}}_{k}^{u} = \operatorname{CE}(\tilde{\mathbf{a}}_{k}^{u}, \mathbf{y}), \\ \tilde{\mathcal{L}}_{k}^{o} = \operatorname{CE}(\tilde{\mathbf{a}}_{k}^{o}, \mathbf{y}). \end{cases}$$
(10)

Moreover, to enhance the discriminative feature learning of each Transformer-based encoder in each module, we also introduce a classifier  $C_m^o$  for each modality. For the early segment action prediction module, utilizing the cross-entropy loss, we have,

$$\begin{cases} \mathbf{a}_{m,k}^{o} = \mathbf{W}_{m}^{o} \mathbf{z}_{m,k}^{o} + \mathbf{b}_{m}^{o}, \\ \mathcal{L}_{m,k}^{o} = \mathrm{CE}(\mathbf{a}_{m,k}^{o}, \mathbf{y}), \end{cases}$$
(11)

where  $\mathbf{a}_{m,k}^{o} \in \mathbb{R}^{N}$  is the predicted action label vector of the early video segment based on its *m*-th modality.  $\mathbf{W}_{m}^{o}$  and  $\mathbf{b}_{m}^{o}$  are the to-be-learned parameters of the action classifier for the *m*-th modality.

Similarly, for the future segment action prediction module, we introduce M classifiers (denoted as  $\mathcal{C}_m^u$ ) and loss function,

$$\begin{cases} \mathbf{a}_{m,k}^{u} = \mathbf{W}_{m}^{u} \mathbf{z}_{m,k}^{u} + \mathbf{b}_{m}^{u}, \\ \mathcal{L}_{m,k}^{u} = \mathrm{CE}(\mathbf{a}_{m,k}^{u}, \mathbf{y}), \end{cases}$$
(12)

where  $\mathbf{a}_{m,k}^{u} \in \mathbb{R}^{N}$  is the predicted action label vector of the future video segment based on its *m*-th modality.  $\mathbf{W}_{m}^{u}$  and  $\mathbf{b}_{m}^{u}$  are the to-be-learned parameters.

## D. Two-stage Training

As aforementioned, we train our model with two stages: mutual enhancement stage and end-to-end aggregation stage. In the former stage, the two modules  $\mathcal{P}^o$  and  $\mathcal{P}^u$  learn from each other for gaining predictive ability iteratively. In the latter stage, we aim to fully integrate the prediction capability of the two modules. IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS FOR VIDEO TECHNOLOGY, VOL. XX, 2023

1) Mutual Enhancement Stage: As aforementioned,  $\mathcal{P}^{o}$  outputs not only the observed feature but also the predicted unobserved feature, while  $\mathcal{P}^{u}$  outputs not only the future video feature but also the predicted feature of the previous early video segment. Intuitively, the learned features of these two modules can be mutually used for guiding each other. Specifically,  $\mathbf{h}_{k}^{o}$  learned by  $\mathcal{P}^{o}$  based on the input early observed video segment can be used for guiding the learning of  $\mathbf{\tilde{h}}_{k}^{o}$  predicted by  $\mathcal{P}^{u}$  based on the future video segment. Conversely,  $\mathbf{h}_{k}^{u}$  derived by  $\mathcal{P}^{v}$ . Thus, we introduce the consistency regularizer to allow the two modules to share knowledge to each other and gain better action prediction capability. The regularizer can be written as follows,

$$\begin{cases} \mathcal{L}_{k}^{fea,o} = \|\mathbf{h}_{k}^{o} - \tilde{\mathbf{h}}_{k}^{o}\|^{2}, \\ \mathcal{L}_{k}^{fea,u} = \|\mathbf{h}_{k}^{u} - \tilde{\mathbf{h}}_{k}^{u}\|^{2}, \\ \mathcal{L}_{k}^{fea} = \mathcal{L}_{k}^{fea,o} + \mathcal{L}_{k}^{fea,u}. \end{cases}$$
(13)

Ultimately, we obtain the final loss function of the early segment action prediction module  $\mathcal{P}^o$  in the mutual enhancement stage as follows,

$$\mathcal{L}_{mut}^{o} = \sum_{k=1}^{K} \left(\frac{1}{M} \sum_{m=1}^{M} \mathcal{L}_{m,k}^{o} + \mathcal{L}_{k}^{o} + \tilde{\mathcal{L}}_{k}^{u} + w^{fea} \mathcal{L}_{k}^{fea}\right), \quad (14)$$

where  $w^{fea}$  is the hyper-parameter.

Similarly, we can obtain the total loss of future segment action prediction module  $\mathcal{P}^u$  as follows,

$$\mathcal{L}_{mut}^{u} = \sum_{k=1}^{K} \left(\frac{1}{M} \sum_{m=1}^{M} \mathcal{L}_{m,k}^{u} + \mathcal{L}_{k}^{u} + \tilde{\mathcal{L}}_{k}^{o} + w^{fea} \mathcal{L}_{k}^{fea}\right).$$
(15)

Notably, inspired by the mutual learning framework, these two modules are optimized alternatively. For each batch, we first freeze  $\mathcal{P}^u$  and only train the early segment action prediction module  $\mathcal{P}^o$  with loss  $\mathcal{L}^o_{mut}$ . Thereafter, we freeze  $\mathcal{P}^o$  and only train the future segment action prediction module  $\mathcal{P}^u$  with loss  $\mathcal{L}^u_{mut}$ . Ultimately, by iterative learning from each other, both two modules can gain the discriminative feature of the full video segment, although their inputs are incomplete.

2) End-to-end Aggregation Stage: In the former stage, the two modules  $\mathcal{P}^o$  and  $\mathcal{P}^u$  iteratively learn from each other for improving their action prediction abilities, respectively. Specifically, the early segment action prediction module should be good at predicting the person's action based on the given partial video segment, while the future segment action prediction module should be skilled in predicting the person's action based on the unobserved future video segment. Although the unobserved future video segment is unavailable in the testing phase, we can predict its feature  $\mathbf{h}_{k}^{u}$  based on  $\mathcal{P}^{o}$ . Accordingly, the future segment action prediction module can enhance the final action prediction in the testing phase by providing the action prediction based on the predicted feature of the unobserved future video segment output by  $\mathcal{P}^{o}$ . Therefore, in the end-to-end aggregation stage, we aim to fully integrate the prediction capability of the two modules.

In addition, we believe that early observed video and future unobserved video segments have different levels of importance



Fig. 4. End-to-end Aggregation Stage

L

for the action prediction. We hence add a fully-connected layer with the sigmoid activation function to learn the trade-off weights between the early action prediction and future action prediction results. In particular, the trade-off weight for the given partial video segment can be obtained as follows,

$$\alpha_k = \text{sigmoid}(\mathbf{W}^e[\mathbf{h}_k^o; \mathbf{h}_k^u] + \mathbf{b}^e), \tag{16}$$

where  $\mathbf{W}^e$  and  $\mathbf{b}^e$  are the to-be-learned parameters, and  $\alpha_k$  represents the importance of early action prediction.

We then can get the final action prediction result for the given partial video segment as follows,

$$\mathbf{a}_{k}^{e} = \alpha_{k} \mathbf{a}_{k}^{o} + (1 - \alpha_{k}) \tilde{\mathbf{a}}_{k}^{u}, \tag{17}$$

where  $\mathbf{a}_{k}^{e} \in \mathbb{R}^{N}$  denotes the final action prediction.

In this stage, we also utilize the cross entropy loss for optimization as follows,

$$\mathcal{L}_{k}^{e} = \mathrm{CE}(\mathbf{a}_{k}^{e}, \mathbf{y}).$$
(18)

Similar to previous mutual enhancement stage, we also consider the classification loss of each single modality to improve the discriminative feature learning. Finally, the loss function of the end-to-end aggregation stage can be written as follows,

$$\mathcal{L}_{agg} = \sum_{k=1}^{K} (\mathcal{L}_{k}^{e} + \frac{1}{M} \sum_{m=1}^{M} \mathcal{L}_{m,k}^{o}).$$
(19)

It is worth noting that in this training stage, we will fix the backbone parameters of the two action prediction modules, but only optimize the aggregation parameters. In this manner, the knowledge obtained from the previous training stage can be well retained. Algorithm 1 summarizes the two-stage training procedure of our model. Page 7 of 12

# IEEE Transactions on Circuits and Systems for Video Technology

IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS FOR VIDEO TECHNOLOGY, VOL. XX, 2023

A	igorithm 1 The Two-stage Training Procedure of Our Model
I	<b>put:</b> Training set $\Omega$ , hyper-parameter $w^{fea}$ .
0	<b>utput:</b> Parameters $\Theta^o$ in $P^o$ , parameters $\Theta^u$ in $P^u$ , weight
V	$V^e$ and bias $\mathbf{b}^e$ .
	: Initialize $\mathcal{T}_m^o$ and $\mathcal{T}_m^u$ with the pretrained parameters for
	each modality m.
	2: repeat
	Semigroup Sample minibatch from $\Omega$ .
	Freeze the parameters $\Theta^u$ and update the parameters
	$\Theta^o$ according to $\mathcal{L}^o_{mut}$ in Eqn.(14).
	5: Freeze the parameters $\Theta^o$ and update the parameters
	$\Theta^u$ according to $\mathcal{L}^u_{mut}$ in Eqn.(15).
	5: until Convergence
	Freeze the parameters in $\mathcal{T}_m^o$ for each modality $m$ .
	3: repeat
	Sample minibatch from $\Omega$ .
1	): Update the parameters $\Theta^o$ , $\mathbf{W}^e$ and $\mathbf{b}^e$ according to
	$\mathcal{L}_{agg}$ in Eqn.(19).
1	: until Convergence

## E. Testing

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59 60 For testing, to enhance the action prediction, apart from the final action prediction result  $\mathbf{a}_k^e$  in Eqn. (13), we also take into account the action prediction result based on each single modality (*i.e.*,  $\mathbf{a}_{m,k}^o$ ). Specifically, we generate the final action prediction result by the linear fusion as follows,

$$\begin{cases} \mathbf{a}_{k} = \gamma \mathbf{a}_{k}^{e} + \sum_{m=1}^{M} \gamma_{m} \mathbf{a}_{m,k}^{o}, \\ \gamma + \sum_{m=1}^{M} \gamma_{m} = 1, \end{cases}$$
(20)

where  $\mathbf{a}_k \in \mathbb{R}^N$  is the final action prediction result for testing.  $\gamma$  and  $\gamma_m$   $(m = 1, \dots, M)$  are the trade-off hyper-parameters.

## **IV. EXPERIMENTS**

In this section, we conducted extensive experiments over the two real-world datasets EPIC-Kitchens55 [33] and EGTEA Gaze+ [34] by answering the following research questions.

- **RQ1**: Does our model outperform state-of-the-art methods?
- **RQ2**: How does each component affect our model performance?
- **RQ3**: How sensitive is our model to the key hyperparameters?
- **RQ4**: What is the intuitive performance of our method?

## A. Experimental Settings

**Datasets.** To evaluate our proposed method, we utilized two large-scale egocentric video benchmarks: EPIC-Kitchens55 [33] and EGTEA Gaze+ [34]. 1) *EPIC-Kitchens55*. Videos of EPIC-Kitchens55 dataset are recorded by 32 participants conducting their non-scripted daily activities in their kitchen environments. It consists of 39,596 video segments annotated by 2,513 action labels in total. As the

 TABLE I

 Three dataset splits of EGTEA Gaze+.

Dataset	Training sets	Testing sets			
EGTEA Gaze+ S1	8,299	2,022			
EGTEA Gaze+ S2	8,299	2,022			
EGTEA Gaze+ S3	8,230	2,021			

testing set of EPIC-Kitchens55 is unavailable, similar to [13], [15], we re-split the public training dataset including 28, 472 video segments, into two parts: 23, 493 video segments for training and 4, 979 video segments for testing. Notably, video segments for training are derived from 232 videos, while that for testing are extracted from the other 40 videos. And 2) *EGTEA Gaze+*. As to the EGTEA Gaze+ [34] dataset, it consists of 10, 328 video segments annotated by 106 action labels. Specifically, EGTEA Gaze+ [34], [35] provides three different dataset splits, as shown in Table I. Each split was randomly sampled from the whole dataset, where 80% of the samples per action is used for training and the rest for testing. Consequently, we comprehensively evaluated our model and baseline methods on these three splits for the EGTEA Gaze+ dataset, respectively.

For both datasets, we uniformly sampled K = 8 video snippets from each action segment. To validate the model performance, we adopted the top-1 accuracy as the evaluation metrics for the following observation ratios (*i.e.*, k/K): 12.5%, 25%, 37.5%, 50%, 62.5%, 75%, 87.5%, and 100%.

Modality Features. We employed four different modalities in the EPIC-Kitchens55 dataset: visual content, flow content, object labels, and audio signals. For fair comparison, we adopted the same features with the work [15]. In particular, we utilized the features of visual content, flow content, and objected labels provided by [13], the dimensions of which are 1,024, 1,024, and 352, respectively. Meanwhile, we used the features of audio modality provided by [16], the dimension of which is 1,024. The four modalities are arranged in the order of "Ivisual modality, flow modality, object modality, audio modality]" as the input of our model. As for the EGTEA Gaze+ dataset, it only provides three modalities of videos, including the visual content, the flow content, and the object labels. Therefore, for this dataset, the input of our model involves three modalities arranged in the order of "*visual* modality, flow modality, object modality]" as the input of our model. We directly adopted the features released by [15]. The dimensions of the visual and flow content features are both 1,024, while that of the object label feature is 352.

**Implementation Details.** For encoding the input sequence of each modality in both datasets, we utilized a Transformer encoder with 2 layers, where the number of attention heads is set to 8. The hidden layer dimension of the Transformer encoder in both datasets is  $d_1 = 768$ . The dimension of the multi-modal fused feature in EPIC-Kitchens55 is  $d_2 = 1024$ , while that in EGTEA Gaze+ is 512. For both datasets, in the mutual enhancement stage, we trained 30 epochs in total. The weight of the consistency regularization is set to  $w^{fea} = 5$ . For EPIC-Kitchens55, we employed the Adam optimizer with an initial learning rate of 0.0001, which multiplies 0.5 at the 15-th and 20-th epochs, respectively. As for EGTEA Gaze+,

# IEEE Transactions on Circuits and Systems for Video Technology

IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS FOR VIDEO TECHNOLOGY, VOL. XX, 2023

8

60

1

TABLE II Performance comparison among different methods in terms of Top-1 accuracy (%) over the EPIC-Kitchens55 dataset with different observation ratios. The best results are highlighted in bold.

Observation ratio	12.5%	25%	37.5%	50%	62.5%	75%	87.5%	100%	avg.
LSTM-late	25.48	29.51	31.54	32.58	33.57	34.45	34.65	34.35	32.02
LSTM-early	24.96	28.18	30.01	31.52	32.92	33.11	33.45	33.17	30.91
RULSTM (Furnari et al. 2022) [13]	24.48	27.63	29.44	30.93	32.16	33.09	33.63	34.07	30.68
RULSTM-audio (Kazakos et al. 2022) [16]	25.46	28.92	31.09	32.90	34.61	35.38	35.78	36.12	32.53
AANet (Kong et al. 2022) [12]	21.38	25.14	28.92	31.09	32.30	33.63	34.11	34.21	30.10
PTSN (Wang et al. 2022) [10]	25.82	29.02	30.95	32.64	34.05	34.73	35.14	34.69	32.13
AKT (Cai et al. 2022) [11]	24.66	27.35	27.19	30.23	31.94	33.61	34.21	34.96	30.52
AKD (Zheng et al. 2022) [15]	27.65	31.26	33.07	34.98	35.90	36.99	37.45	37.55	34.36
TRACE	28.74	33.00	36.02	37.33	38.35	39.08	39.26	39.66	36.43



Fig. 5. Performance comparison among different methods with different observation ratios on the (a) EGTEA Gaze+ S1, (b) EGTEA Gaze+ S2 and (c) EGTEA Gaze+ S3, respectively.

the initial learning rate is set to 0.0001, which multiplies 0.5at the 9-th and 12-th epochs, respectively. The batch size for EPIC-Kitchens55 and EGTEA Gaze+ is set to 256 and 128, respectively. The dropout rate of the model for EPIC-Kitchens55 and EGTEA Gaze+ is set to 0.3 and 0.15, respectively. In the end-to-end aggregation stage, for both datasets, we froze all the parameters of the Transformer encoder, and the initial integration weight of the fully-connected layer is set to 0. For EPIC-Kitchens55, we trained 80 epochs in total. The dropout rate in this stage is set to 0.95 and the batch size is set to 1024. For EGTEA Gaze+, the number of training epochs is set to 20, the dropout rate is set to 0.9, and the batch size is set to 1024. In this stage, we also employed Adam optimizer for both datasets. The learning rate for EPIC-Kitchens55 and EGTEA Gaze+ was gradually improved to 0.0004 and 0.0007, respectively, by using the warmup strategy in the first four epochs and maintaining till the end. Ultimately, for EPIC-Kitchens55, the trade-off hyperparameter for the multi-modal action prediction in Eqn. (20) is set to  $\gamma = 0.48$ , while that for the single-modal action predictions (*i.e.*,  $\{\gamma_m\}$ ) are set to  $\{0.02, 0.10, 0.18, 0.22\}$ , respectively. Pertaining to EGTEA Gaze+, the trade-off hyperparameter  $\gamma = 0.6$ , while that for the single-modal action predictions (*i.e.*,  $\{\gamma_m\}$ ) are set to  $\{0.12, 0.27, 0.01\}$ , respectively.

## B. On Model Comparison (RQ1)

To validate the effectiveness of our proposed methods, we chose the following baselines for comparison.

- **LSTM-late.** This baseline utilizes a one-layer LSTM with the size of the hidden layer as 1,024 for each modality and fused all the modalities with the late fusion strategy.
- **LSTM-early.** Similar to LSTM-late, this method adopts the early fusion strategy to concatenate the feature vectors of all modalities.
- **RULSTM.** This method utilizes a rolling-unrolling LSTM architecture to solve the egocentric action anticipation task, which jointly explores three modalities (*i.e.*, flow contents, visual contents and object labels) of the video segment.
- RULSTM-audio. As for a fair comparison, we design this baseline by extending RULSTM to incorporate the audio signal modality.
- **PTSN.** This baseline, devised for early action prediction from the third-person view, uses a teacher-student learning block for distilling progressive knowledge from teacher to student, where the teacher is an action recognition model and the student is the to-be-learned early action prediction model.
- **AANet.** This is an adversarial action prediction framework, which aims to learn the representative and discriminative features to enhance the performance of early action prediction from the third-person view.
- **AKT.** This baseline employs the knowledge transfer learning from fully observed videos to boost the third-person view early action prediction performance.
- AKD. This is a multi-modal adversarial knowledge dis-

TABLE III ABLATION STUDY RESULTS OVER THE EPIC-KITCHENS55 DATASET.

Observation ratio	12.5%	25%	37.5%	50%	62.5%	75%	87.5%	100%	Avg.
w/o Pre-training	28.64	32.46	35.04	36.56	37.41	38.48	38.74	39.20	35.82
w/o Single-Modal Classification	27.84	31.86	34.43	35.96	36.89	37.83	38.19	37.17	35.02
w/o Consistency Regularizer	28.76	32.32	34.69	36.20	36.93	37.47	37.85	38.21	35.31
w/o Mutual Enhancement Stage	27.80	31.62	33.71	35.94	36.77	37.01	37.43	37.57	34.73
w/o End-to-end Aggregation Stage	28.78	32.68	35.66	37.13	37.95	38.46	38.98	39.02	36.08
TRACE	28.74	33.00	36.02	37.33	38.35	39.08	39.26	39.66	36.43

tillation framework for egocentric early action prediction, which involves a teacher network to learn a comprehensive video representation based on the multi-modal full video segment, and a student network to predict the action only based on the partial video segment.

Table II and Figure 5 show the performance comparison among different methods in terms of Top-1 accuracy (%) over the EPIC-Kitchens55 dataset and EGTEA Gaze++ dataset with different observation ratios, respectively. As can be seen, our TRACE model almost consistently outperform all the baseline methods on all observation ratios, which demonstrates the effectiveness of the proposed Transformer-based dual action prediction model for the egocentric early action prediction. Specifically, on average, our TRACE model exceeds the best baseline (i.e., AKD) by 2.07% regarding the Top-1 accuracy on the EPIC-Kitchens55 dataset. This may be due to three reasons. 1) All the baseline methods adopted LSTM as the backbone for encoding the video segment, while our TRACE model utilizes the Transformer encoder, which can model the non-sequential correlations among the discrete snippets in the video segment. 2) Different from all the baselines, our TRACE model incorporates the correlation modeling between the observed video segment and unobserved video segment with two separate multi-modal features. 3) Beyond all the baseline methods, we optimize the model by two stages, where the two action prediction modules (i.e., early segment action prediction module and future segment action prediction module) can mutually share knowledge to each other, and fully aggregated in the testing phase.

## C. On Ablation Study (RQ2)

We conducted the ablation study on our model with the following model derivatives. 1) w/o Pre-training: To verify the effectiveness of autoregressive pre-training, we randomly initialized all the Transformer parameters and then adopted the two-stage optimization training. 2) w/o Single-Modal Classification: To explore the function of the single-modal classifications, we removed the losses of single-modal classifications in both training stages, and eliminated the single-modal action prediction results in the testing phase. 3) w/o Consistency **Regularizer**: To justify the effect of  $\tilde{\mathbf{h}}_k^u$ , we removed the feature consistency regularization from the mutual learning enhancement stage. 4) w/o Mutual Enhancement Stage: To study the impact of the mutual learning enhancement stage, we removed the mutual learning enhancement training stage and directly carried out the end-to-end aggregation training stage. In this derivative, to improve the modal capacity, the

parameters of the Transformer were not frozen in the training stage. And 5) w/o End-to-end Aggregation Stage: Similarly, to investigate the effect of end-to-end aggregation stage, we directly removed the end-to-end aggregation training stage.

Table III summarizes the ablation study results over the EPIC-Kitchens55 dataset. It can be seen that our methods consistently outperforms all the derivatives, which demonstrates the effectiveness of each component in our proposed model. Specifically, we had the following four detailed observations. 1) The performance of w/o Pre-training and w/o Single-Modal Classification drop largely, which indicates that the autoregressive pre-training does improve the feature encoding capability of the Transformer encoder in the dual action prediction modules, and the single-modal classification is indeed effective in enhancing the discriminative feature learning of our model. 2) w/o Consistency Regularizer performs much worse than our model, which validates that the consistency regularizer is useful in allowing the two action prediction modules to share knowledge with each other and hence gaining better action prediction performance. 3) Both w/o Mutual Enhancement Stage and w/o End-to-end Aggregation Stage perform inferior to our method, which indicates that it is essential to design the two-stage optimization paradigm.

## D. On Sensitivity Analysis (RQ3)

Besides, we studied the sensitivity of our model pertaining to the number of heads and the number of layers of the Transformer encoder, as well as the trade-off hyperparameter for the consistency regularizer in Eqn. (14) and Eqn. (15) with the EPIC-Kitchens55 dataset.

1) On the number of heads of Transformer encoder: We varied the number of heads in the transformer model in the range of  $\{1, 2, 4, 8, 16, 32\}$ . Figure 6(a) shows the performance of our model with different number of heads in terms of the average top-1 accuracy. As can be seen, with the increase of the number of heads used in the Transformer encoder, the performance of our model increases first and then decreases. In the end, our model achieves the optimal performance when the number of heads is 8. When the number of heads is larger than 8, the model's performance slightly drops. This may be due to too many heads may lead to the overfitting issue.

2) On the number of layers of Transformer encoder: To learn the impact of the number of layers used in the Transformer encoder, we changed the number of layers from 1 to 5 with the step of 1. As can be seen from Figure 6(b), our model performs best when the number of layers in Transformer

# IEEE Transactions on Circuits and Systems for Video Technology





Fig. 6. Performance of our model with different numbers of heads and layers of the Transformer encoder, as well as different trade-off weight values of  $w^{fea}$  for the consistency regularizer.



Fig. 7. Action predictions of our model and the best baseline AKD for three testing examples in the EPIC-Kitchens55 dataset, where all observation ratios have been tested for comprehensive comparison. For a clear illustration, we present the frames of the corresponding observation ratios for all the examples. Incorrect predictions have been highlighted in red.

encoder is 2. One likely reason is also that too many layers E. Can lead to the overfitting problem.

3) On the trade-off hyperparameter for consistency regularizer  $w^{fea}$ : To explore the effect of the trade-off hyperparameter in controlling the balance between the cross-entropy losses and the consistency regularizer in the optimization of the mutual enhancement stage, we tuned the trade-off hyperparameter around the optimal value 5. In particular, we varied the trade-off hyperparameter from 1 to 9 with the step of 2. As can be seen from Figure 6(c), the performance of our model first goes better with the increase of the hyperparameter, and then goes worse with the continue increase. This is reasonble as the too small  $w^{fea}$  cannot guarantee the knowledge transferring between the too modules, while too large  $w^{fea}$  may downgrade the discriminative feature learning towards action prediction.

# V layers E. On Case Study (RQ4)

To gain the intuitive understanding of our TRACE model for the task of egocentric early action prediction, we reported the action predictions of our model and the best baseline AKD on three testing cases in the EPIC-Kitchens55 dataset, where all observation ratios have been tested for comprehensive comparison. As we can see from Fig 7(a), the person is cutting an onion in the video segment. As "cutting onion" is an action that is easy to recognize, both our model and AKD given the correct predictions at all observation ratios. This indicates that both our model and AKD can predict correctly in the relatively simple and obvious case. For the more complex and difficult case in Fig 7(b), where the to-be-recognized action "take lid" is highly similar to "put lid", our model can correctly predict the on-going action " take lid" by observing only 12.5% snippets, while the baseline method AKD has to observe 37.5% snippets. This confirms the effectiveness of our Transformer-based dual action prediction model in modeling the correlations between the observed and unobserved video

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59 60 segments. Fig 7(c) shows a failure case of our model. As can be seen, compared with AKD, our model fails to predict the action labels at all observation ratios. By analyzing the video content, we noticed that for this case, our predicted ongoing action "take pizza" is correct, while the ground truth label "put-down pizza" should be accidentally annotated and is a noisy label. This also reflects the capability of our TRACE model in solving the task of egocentric early action prediction.

# V. CONCLUSION AND FUTURE WORK

In this paper, we present a novel TransfoRmer-based duAl aCtion prEdiction (TRACE) model for the task of egocentric early action prediction, which involves two key modules: the early (observed) segment action prediction module and the future (unobserved) segment action prediction module. Both modules adopt the Transformer encoders to encode the video segment. To model the coherence of the full video segment, we introduce a consistency regularizer between the two modules. Moreover, to boost the performance, we design a two-stage optimization scheme, including the mutual enhancement stage and end-to-end aggregation stage. Extensive experiments on two public datasets have demonstrated the superiority of our proposed model, and the benefit of incorporating Transformer encoder, consistency regularizer, pre-training as well as the two-stage training. Currently, in this work, we directly adopted existing autoregresssive pre-training technique to pre-train our model. In the future, we plan to investigate more advanced pretraining scheme to further promote the model performance.

## REFERENCES

- Z. Yang, Y. Li, J. Yang, and J. Luo, "Action recognition with spatiotemporal visual attention on skeleton image sequences," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 29, no. 8, pp. 2405–2415, 2019.
- [2] J. Weng, X. Jiang, W. Zheng, and J. Yuan, "Early action recognition with category exclusion using policy-based reinforcement learning," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 30, no. 12, pp. 4626–4638, 2020.
- [3] S. Li, K. Li, and Y. Fu, "Early recognition of 3d human actions," ACM Trans. Multim. Comput. Commun. Appl., vol. 14, no. 1s, pp. 20:1–20:21, 2018.
- [4] Y. Tang, Z. Wang, J. Lu, J. Feng, and J. Zhou, "Multi-stream deep neural networks for RGB-D egocentric action recognition," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 29, no. 10, pp. 3001–3015, 2019.
- [5] M. Wang, C. Luo, B. Ni, J. Yuan, J. Wang, and S. Yan, "First-person daily activity recognition with manipulated object proposals and nonlinear feature fusion," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 28, no. 10, pp. 2946–2955, 2018.
- [6] X. Wang, L. Zhu, H. Wang, and Y. Yang, "Interactive prototype learning for egocentric action recognition," in *Proc. IEEE Int. Conf. Comput. Vis.* (*ICCV*). IEEE, 2021, pp. 8148–8157.
- [7] T. Liu, K. Lam, R. Zhao, and J. Kong, "Enhanced attention tracking with multi-branch network for egocentric activity recognition," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 32, no. 6, pp. 3587–3602, 2022.
- [8] W. Morales-Alvarez, F. M. Moreno, O. Sipele, N. Smirnov, and C. Olaverri-Monreal, "Autonomous driving: Framework for pedestrian intention estimation in a real world scenario," in *IEEE Intelligent Vehicles Symposium*. IEEE, 2020, pp. 39–44.
- [9] A. Rasouli, I. Kotseruba, and J. K. Tsotsos, "Pedestrian action anticipation using contextual feature fusion in stacked rnns," in *Proc. 30th Brit. Mach. Vis. Conf. (BMVC)*. BMVA Press, 2019, p. 171.
- [10] X. Wang, J. Hu, J. Lai, J. Zhang, and W. Zheng, "Progressive teacherstudent learning for early action prediction," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR).* IEEE, 2019, pp. 3556–3565.
- [11] Y. Cai, H. Li, J. Hu, and W. Zheng, "Action knowledge transfer for action prediction with partial videos," in *Proc. AAAI Conf. Artif. Intell.* (AAAI). AAAI Press, 2019, pp. 8118–8125.

- [12] Y. Kong, Z. Tao, and Y. Fu, "Adversarial action prediction networks," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 42, no. 3, pp. 539–553, 2020.
- [13] A. Furnari and G. M. Farinella, "What would you expect? anticipating egocentric actions with rolling-unrolling lstms and modality attention," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*. IEEE, 2019, pp. 6251– 6260.
- [14] A. Furnari and G. M. Farinella, "Rolling-unrolling lstms for action anticipation from first-person video," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 43, no. 11, pp. 4021–4036, 2021.
- [15] N. Zheng, X. Song, T. Su, W. Liu, Y. Yan, and L. Nie, "Egocentric early action prediction via adversarial knowledge distillation," ACM Trans. Multim. Comput. Commun. Appl., vol. 1, no. 1, pp. 1–16, 2022.
- [16] E. Kazakos, A. Nagrani, A. Zisserman, and D. Damen, "Epic-fusion: Audio-visual temporal binding for egocentric action recognition," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*. IEEE, 2019, pp. 5491– 5500.
- [17] H. Fan, B. Xiong, K. Mangalam, Y. Li, Z. Yan, J. Malik, and C. Feichtenhofer, "Multiscale vision transformers," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV).* IEEE, 2021, pp. 6804–6815.
- [18] R. Girdhar and K. Grauman, "Anticipative video transformer," in Proc. IEEE Int. Conf. Comput. Vis. (ICCV). IEEE, 2021, pp. 13485–13495.
- [19] M. Huang, S. Su, H. Zhang, G. Cai, D. Gong, D. Cao, and S. Li, "Multifeature selection for 3d human action recognition," ACM Trans. Multim. Comput. Commun. Appl., vol. 14, no. 2, pp. 45:1–45:18, 2018.
- [20] Y. Kong, Z. Tao, and Y. Fu, "Deep sequential context networks for action prediction," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit.* (CVPR). IEEE, 2017, pp. 3662–3670.
- [21] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin, "Attention is all you need," in *Proc. Neural Inf. Process. Syst. (NeurIPS).* MIT Press, 2017, pp. 5998–6008.
- [22] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly, J. Uszkoreit, and N. Houlsby, "An image is worth 16x16 words: Transformers for image recognition at scale," in *Proc. 9th Int. Conf. Learn. Represent. (ICLR)*. OpenReview.net, 2021, pp. 1–21.
- [23] H. Touvron, M. Cord, M. Douze, F. Massa, A. Sablayrolles, and H. Jégou, "Training data-efficient image transformers & distillation through attention," in *Proc. 34th Int. Conf. Mach. Learn. (ICML)*. PMLR, 2021, pp. 10347–10357.
- [24] J. Yu, J. Li, Z. Yu, and Q. Huang, "Multimodal transformer with multiview visual representation for image captioning," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 30, no. 12, pp. 4467–4480, 2020.
- [25] S. Cao, G. An, Z. Zheng, and Z. Wang, "Vision-enhanced and consensusaware transformer for image captioning," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 32, no. 10, pp. 7005–7018, 2022.
- [26] Z. Liu, Y. Tan, Q. He, and Y. Xiao, "Swinnet: Swin transformer drives edge-aware RGB-D and RGB-T salient object detection," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 32, no. 7, pp. 4486–4497, 2022.
- [27] L. Zhao, J. Guo, D. Xu, and L. Sheng, "Transformer3d-det: Improving 3d object detection by vote refinement," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 31, no. 12, pp. 4735–4746, 2021.
- [28] D. Roy and B. Fernando, "Action anticipation using pairwise humanobject interactions and transformers," *IEEE Trans. Image Process.*, vol. 30, pp. 8116–8129, 2021.
- [29] Z. Yuan, X. Song, L. Bai, Z. Wang, and W. Ouyang, "Temporal-channel transformer for 3d lidar-based video object detection for autonomous driving," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 32, no. 4, pp. 2068–2078, 2022.
- [30] J. Yu, J. Li, Z. Yu, and Q. Huang, "Multimodal transformer with multiview visual representation for image captioning," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 30, no. 12, pp. 4467–4480, 2020.
- [31] C. Vondrick, H. Pirsiavash, and A. Torralba, "Anticipating visual representations from unlabeled video," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR).* IEEE, 2016, pp. 98–106.
- [32] R. Girdhar and K. Grauman, "Anticipative video transformer," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*. IEEE, 2021, pp. 13485–13495.
- [33] D. Damen, H. Doughty, G. M. Farinella, S. Fidler, A. Furnari, E. Kazakos, D. Moltisanti, J. Munro, T. Perrett, W. Price, and M. Wray, "Scaling egocentric vision: The dataset," in *Proc. Eur. Conf. Comput. Vis. (ECCV).* Springer, 2018, pp. 753–771.
- [34] Y. Li, M. Liu, and J. M. Rehg, "In the eye of beholder: Joint learning of gaze and actions in first person video," in *Proc. Eur. Conf. Comput. Vis. (ECCV).* Springer, 2018, pp. 639–655.
- [35] Yin Li and Miao Liu and James M. Rehg, "In the eye of beholder: Gaze and actions in first person video," *IEEE Trans. Pattern Anal. Mach. Intell.*, pp. 1–16, 2021.



SIGIR, and IEEE TIP.

Weili Guan received the master degree from National University of Singapore. After that, she joined Hewlett Packard Enterprise in Singapore as a Software Engineer and worked there for around five years. She is currently a PhD student with the Faculty of Information Technology, Monash University (Clayton Campus), Australia. And She is also an intern in Pengcheng Laboratory now. Her research interests are multimedia computing and information retrieval. She has published many papers at the first-tier conferences and journals, like ACM MM,

IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS FOR VIDEO TECHNOLOGY, VOL. XX, 2023



Yaowei Wang received the Ph.D. degree in computer science from the University of Chinese Academy of Sciences in 2005. He worked with the Department of Electronics Engineering, Beijing Institute of Technology, from 2005 to 2019. Currently, he is a professor with the Peng Cheng Laboratory, Shenzhen, China. He servers the chair of the IEEE Digital Retina Systems Working Group and a member of IEEE, CIE, CCF, CSIG. He was the recipient of the second prize of the National Technology Invention in 2017 and the first prize

of the CIE Technology Invention in 2015. He has co-authored more than 120 technical articles in international journals and conferences, including IEEE TIP, CVPR, ICCV, etc. His research interests include machine learning, multimedia content analysis and understanding. He promoted the digital retina technology, made efforts to establish system standards for Digital Retina. He trained a vision model named "Pengcheng · Dasheng" with 1 billion parameters, achieving an over 10% performance gain in the detection and recognition task in more than 20 application scenarios. He led the development of the first digital retina verification system, which has been applied to the urban traffic management field of over 30 large and medium-sized cities in China.



Xuemeng Song received the B.E. degree from the University of Science and Technology of China, in 2012, and the Ph.D. degree from the School of Computing, National University of Singapore, in 2016. She is currently an Associate Professor with Shandong University, China. She has published several papers in the top venues, such as ACM SIGIR, MM, and TOIS. Her research interests include information retrieval and social network analysis. She has served as a reviewer for many top conferences and journals. She is also an AE of IET Image Processing.



Kejie Wang is currently pursuing the B.Eng. degree in computer science from the Shandong University. His research interest is multimedia computing.



Haokun Wen received the B.E. degree from the Ocean University of China, in 2019, and the master's degree from the School of Computer Science and Technology, Shandong University, in 2022. He is currently pursuing the Ph.D. degree with the Department of Computer Science and Technology, Harbin Institute of Technology (Shenzhen). His research interests include multimedia computing and information retrieval. He has published several papers in top venues, such as ACM SIGIR, ACM MM, IEEE TIP, and ACM TOMM.



Xiaojun Chang is a Professor in Australian Artificial Intelligence Insitute, Faculty of Engineering and Information Technology, University of Technology Sydney. He is the Director of the ReLER Lab. He is also an Honorary Professor in the School of Computing Technologies, RMIT University, Australia. Before joining UTS, he was an Associate Professor at School of Computing Technologies, RMIT University, Australia. After graduation, he subsequently worked as a Postdoc Research Fellow at School of Computer Science, Carnegie Mellon University,

Lecturer and Senior Lecturer in the Faculty of Information Technology, Monash University, Australia. He has focused his research on exploring multiple signals (visual, acoustic, textual) for automatic content analysis in unconstrained or surveillence videos. His team has won multiple prizes from international grand challenges which hosted competitive teams from MIT, University of Maryland, Facebook AI Research (FAIR) and Baidu VIS, and aim to advance visual understanding using deep learning. For example, he won the first place in the TrecVID 2019 - Activity Extended Video (ActEV) challenge, which was held by National Institute of Standards and Technology, US.



Hongda Ni is currently pursuing the B.Eng. degree in computer science from the Harbin Institute of Technology (Shenzhen). His research interests include multimedia computing and natural language processing.

1 2